## **Anti Cross Thread Tool NEW!**


DATE: Nov.4th 2021

- Patented Anti Cross Thread Function
- Reducing the work hour without hand-tightened
- Improving the product's quality




## **Enables prevent the cross thread**


The tool have a fuction to prevent the cross thread by sensing the upright condition of the bolt with the built-in sensor.




## Reducing the work hour without hand-tightened

The sensor catches the vibration to check if the bolt is in upright condition before tightening starts by reverse rotation. After confirming the right condition, it will start tightening with forward rotation. This function enables to skip manual temporary tightening and makes "single shot tightening".







## Improving the product's quality

Use the Anti Cross function to confirm the upright condition of the bolt. By setting the upper and lower limits of the screw rotation ridges from screw from start to complete the tightening, the washer shortage & bolt length can be detected. It can help to reduce the defective product and improve the quality.





M8 with washer
Rotation ridges: 13.06



M8 without washer Rotation ridges: 14.35

Controller: V1.417 User Console: V1.163

Note) The specifications and design of the product may be changed without notice.

Please add "GA" to the model as below: e.g. Pistol type: HFT-015M50-P1-GA (-CE) Angle type: HFT-015M50-A1-20-GA (-CE) Straight type: HFT-015M50-S1-20-GA (-CE)





1-54-1, Shimoishihara, Chofu-City, Tokyo 182-0034 Japan TEL:+81-424-40-1465 FAX:+81-424-40-1436

URL:http://www.daiichi-dentsu.co.jp E-mail:sales@daiichi-dentsu.co.jp

