

Launching New Tools for Hand-held Nutrunner

Date : October 10th, 2017

- Four models of angle tools : 80, 130, 200, 300 Nm
- Three models of straight tools : 55, 90, 130 Nm



HFT-130M120-S-20

HFT-130M120-A-20

HFT-200M120-A-20

HFT-300M120-A-20

Tool specifications

Angle tool

	Model	Torque Range (Nm)	Max Speed (rpm)	Total Length (mm)	Weight (kg)	Square Drive (mm)
	HFT-015M50-A1-20	15.0	1215	369.0	1.60	□ 9.5 (3/8")
	HFT-025M80-A1-20	25.0	1070	389.0	1.70	□ 9.5 (3/8")
	HFT-040M80-A1-20	40.0	648	414.0	1.93	□ 9.5 (3/8")
	HFT-060M80-A-20	60.0	446	414.0	1.95	□12.7 (1/2")
NEW	HFT-080M120-A-20	80.0	557	459.8	3.00	□12.7 (1/2")
NEW	HFT-130M120-A-20	130.0	316	484.8	3.30	□12.7 (1/2")
NEW	HFT-200M120-A-20	200.0	206	512.3	3.70	□15.9 (5/8")
NEW	HFT-300M120-A-20	300.0	144	586.0	6.20	□19.0 (3/4")

Straight tool

	Model	Torque Range (Nm)	Max Speed (rpm)	Total Length (mm)	Weight (kg)	Square Drive (mm)
	HFT-010M50-S1-20	10.0	1800	331.0	1.30	□ 9.5 (3/8")
	HFT-015M80-S1-20	15.0	1600	351.0	1.40	□ 9.5 (3/8")
	HFT-025M80-S-20	25.0	1000	351.0	1.43	□ 9.5 (3/8")
	HFT-040M80-S-20	40.0	694	351.0	1.43	□ 9.5 (3/8")
NEW	HFT-055M120-S-20	55.0	861	404.5	(2.40)	□12.7 (1/2")
NEW	HFT-090M120-S-20	90.0	488	417.5	(2.70)	□12.7 (1/2")
NEW	HFT-130M120-S-20	130.0	318	417.5	2.70	□12.7 (1/2")

Controller

The only model described below can operate the new tools.

Model: HFC-B024A-*-*-*

Cable

Our present cables are compatible.



ELECTRICAL ASSEMBLY TOOLS
DAI-ICHI DENTSU LTD.

NUTRUNNER / HAND-HELD TOOL / SERVO PRESS

Headquarters

1-54-1, Shimoishihara, Chofu-City, Tokyo 182-0034 Japan
TEL: +81-424-40-1465 FAX: +81-424-40-1436
URL : <http://www.daiichi-dentsu.co.jp>
E-mail: sales@daiichi-dentsu.co.jp

Kani Plant

690-1 Omori, Kani-City, Gifu, 509-0238 Japan
TEL: +81-574-62-5865 FAX: +81-574-62-3523

